

KERSTEN®

Generator

DG 309



THE PRODUCT

The driving force for your discharge.
The high-voltage generators provide the electrical supply for all KERSTEN discharging components.
Error information for generator and components is included.

BENEFITS

- regulated DC Voltage
- 6 high voltage slots
- Plug-in System
- Highest output of ions

CUSTOMER BENEFITS

- No EMC problems
- Installation in the smallest of spaces
- Flexible expansion options
- Maintenance free

GENERAL INFORMATION

Supply voltage	U_{enn}	V DC	24+-10%
Max. operating current	I_{h}	A	2.3
Max. active power	P	W	56
Control voltage	U_{st}	V DC	24+-10%
Max. current control circuit	I_{st}	A	1,0
Error output voltage	U_{f}	V DC	24+-10%
Max. error output voltage	I_{f}	A	0.4
Error output voltage inverted	U_{fi}	V DC	24+-10%
Max. error output voltage inverted	I_{fi}	A	0.4

DETAILS

Max. Output voltage	U_{a}	kV DC	9
Max. output voltage	I_{max}	mA	1,46
Type of protection			IP54
Number of high voltage slots			6
Type of connection			neXt® - Stecksystem

CLIMATE CONDITIONS


Temperature during transport and storage	T	°C / °F	-25 - +85 / -13- +185*
Temperature during operation	T	°C / °F	++5 - +50 / +41- +122**
relative humidity (non-condensing)	RH	%	<80

DIMENSIONS

	L/W/H	mm	150/120/51
--	-------	----	------------

* acc. to UL50 Type B / Class 3K3 max. 70 °C (+158 °F) ** acc. to UL50 Type B / Class 3K3 max. 40 °C (+104°F)

TECHNICAL DRAWING



All dimension
measurements in mm

KERSTEN ELEKTROSTATIK GMBH

Walter-Knoell-Straße 3
D-79115 Freiburg | Germany
T +49 761 47944-0 | F +49 761 47944-99
info@kersten.de | www.kersten.de

